



Specification

1. Voltage 12V, no-load current 2.4A, no-load speed $4200 \pm 10\%$; Noise 62dB(A);
2. Torque 0.4Nm, Current less than 23A, Speed $3000 \pm 10\%$;
3. Hi-pot 600V, 50Hz, 1s when the resistance of motor is more than $20M\Omega$
4. No abnormal noise.
5. Surface clean without any damages.
6. Can be assembled with MCP4 gearbox if required (dimensions in page 2)

| | | | | | | | | | |
|----|----|-------|-----|-----------|---------------------------|----|-----|---|--|
| | | | | | PMDC Brushed Motor | | | Motion Control Products Ltd 11-15 Francis Ave. Bournemouth Dorset, UK, BH11 8NX TEL.: +44 (0)1202 599922 motioncontrolproducts.com | |
| | | | | | 90ZYT155-12-3000 / | | | | |
| | | | | | 90ZYT155-24-3000 | | | | |
| 标记 | 处数 | 更改文件号 | 签名 | 年月日 | 阶段标记 | 数量 | 比例 | | |
| 设计 | | | 标准化 | 2017-6-23 | | | 1:1 | | |
| 校对 | | | | | | | | | |
| 审核 | | | | | | | | | |
| 工艺 | | | 批准 | | 共 张 第 张 | | | Outline Drawing | |

